

Specifications 740A				Specifications 750A			
MODEL (working width)	6 m	8 m	9 m	MODEL (working width)	3 m	4 m	6 m
Seed hopper	2300 l	3500 l	3500 l	Seed hopper capacity	1800 l	1800 l	2300 l
Seed grain application	Air seeding system			Seed grain application	Air seeding system		
Seed rate	2 up to 380 kg/hectare			Seed rate	2 up to 380 kg/hectare		
Openers	Double disc, 343 mm diameter, 6 mm offset, 10° blade angle			Openers	18 single discs	24	36
Number	40	52	60	Disc diameter	457 mm	457 mm	457 mm
Spacing	15 cm	15, 3 cm	15 cm	Row spacing	16,6 cm	16,6 cm	16,6 cm
Pattern	Staggered			Seeding depth	13 – 90 mm		
Seeding depth	6 – 78 mm			Depth settings	13 (6 mm increments)		
Depth control	Depth gauging press wheel			Down pressure system	Active hydraulic down pressure system		
Depth settings	13 (6 mm) increments, single hand adjustment			Opener down pressure	0 – 250 kg per opener, infinitely variable		
Down pressure system	Active hydraulic down pressure system			Row markers	Heavy duty	Heavy duty	Heavy duty
Opener down pressure	0 – 50 kg per opener, infinitely variable				hydraulic fold shear bolt	hydraulic fold shear bolt	hydraulic bi-fold shear bolt
Markers	Heavy duty hydraulic, shearbolt protected						
	bi-fold	tri-fold	tri-fold	Transport width	3 m	3 m	3 m
Transport width	3 m	3 m	3 m	Length	6,1 m	6,1 m	6,1 m
Height	2,9 m	3,6 m	4 m	Height	2,96 m	3,96 m	4 m
Wheels	standard	Four 31-13 5x15		Transport wheels	Two	Four	Four
	option	Four 31-15 5x15 terra tyres		Brakes	Air or hydraulic	Air or hydraulic	Air or hydraulic
Brake system	Air or hydraulic			Weight	2900 kg	4500 kg	6300 kg
Weight	3000 kg	3600 kg	3900 kg	Extra ballast	Up to 500 kg	Up to 500 kg	Up to 500 kg
Tractor requirement (min.)	100 hp	120 hp	130 hp	Tractor requirement	80 hp	110 hp	140 hp
Options	Harrow with 10 mm tines, Electro-magnetic marker lift control, Track eradicators, Pre-Emergence markers, Press-wheel scrapers, Dual (8 and 9 m) and triple (9 m) wing gauge wheels, Greenstar Drill Control system ISOBUS, no marker arm option			Options	Electro-magnetic lift control, Greenstar Drill Control system ISOBUS, no marker arm option		

The 740A drill for seeding in conventional or minimum till.

The 750A drill – precise seed placement on conventional till through to no-till.