

OFF ROAD Construction N45

N45

89 kW (121 HP) @ 2200 rpm

Stage IV / Tier 4 Final

SPECIFICATIONS

No. of cylinders / valves	4L / 4	
Aspiration	WG	
Injection System	COMMON RAIL 1600 bar	
Displacement	liters	4.5
Bore per Stroke	millimeters	104 x 132
Rated power	kW (HP) @ rpm	89 (121) @ 2200
Peak torque	Nm (kgm) @ rpm	539 (56) @ -
ATS	HI-eSCR	
Certification	Stage IV / Tier 4 Final	

WEIGHT AND DIMENSIONS


Dimensions (L x W x H)	mm	816 x 687 x 1049
Dry Weight	Kg	402

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

POWER & TORQUE



CONSTRUCTION

Do you want to know more?



LEGEND

Air Handling

- TC (Turbocharged)
- NA (Naturally Aspirated)
- TCA (Turbocharged with aftercooler)

Turbocharger

- WG (Wastegate)
- VGT (Variable Geometry Turbocharger)
- TST (Twin Stage Turbocharge)

Exhaust System

- EGR (Exhaust Gas Recirculation)
- SCR (Selective Catalytic Reduction)
- DPF (Diesel Particulate Filter)
- DOC (Diesel Oxidation Catalyst)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

