

Specifications

MODEL		DS4110	DS4510
ENGINE			
Model		4A200LWM	4A220LWM
Type		4Cyl., In-line Vertical, Water-cooled 4-cycle diesel engine	4Cyl., In-line Vertical, Water-cooled 4-cycle diesel engine
Engine gross	HP	41	45
PTO	HP	31.4/2,600	35.1/2,600
Displacement	cc	1,999	2,197
Rated revolution	rpm	2,600	2,600
Fuel tank capacity	ℓ	42	42
DRIVE TRAIN			
Clutch		Dry single stage	Dry single stage
Transmission		Constant Mesh	Constant Mesh
Speeds		F8/R8	F8/R8
Differential lock		Rear Standard	Rear Standard
Brake		Wet disc	Wet disc
PTO		Hydraulic, Independent	Hydraulic, Independent
Rear PTO (standard)	rpm	540	540
HYDRAULIC SYSTEM			
Pump		Gear(Tandem)	Gear(Tandem)
Pump capacity(Max. flow rate)	ℓ / min	49.9	49.9
3-point hitch		Cat. I	Cat. I
Maximum Lift Capacity at 24"aft of hitch	kg	1,100	1,100
Hydraulic lift control system		Position control	Position control
Steering		Hydrostatic Power Steering	Hydrostatic Power Steering
TIRE SIZE			
Front AG.		8-16	8-16
Rear AG.		13.6-24	13.6-24
TRAVELING SPEEDS			
Forward	km/h	1.75-24.14	1.75-24.14
Reverse	km/h	1.62-22.26	1.62-22.26
DIMENSIONS			
Overall length(includes 3-pt hitch)	mm	3,168.5	3,168.5
Overall width(minimum tread)	mm	1,574	1,574
Overall height(from top of ROPS)	mm	2,521	2,521
Wheelbase	mm	1,850	1,850
Min. ground clearance	mm	348	348
Tread	mm	1,246	1,246
Front(AG)	mm	1,170-1,480	1,170-1,480
Rear(AG)	mm	1,170-1,480	1,170-1,480
Min. turning radius(with brake)	m	3.0	3.0
Weight with ROPS and tires	kg	1,600	1,605



Standard Equipment

- Single Remote Hyd. Valve
- Parking brake
- Draw bar
- Foldable Rops with Seat Belt
- Horn
- Head Lamp
- 7 pin socket
- Rear View Mirror

Optional Equipment

- 2nd Remote Hyd. Valve
- Front Suit Case Weight
- Rear Wheel Weight
- Sunshade
- Working Lamp

KIOTI
run ahead of the pack

KIOTI VALUE TRACTOR
DS4110/DS4510



Kioti Tractor / Daedong Ind. Co., Ltd. / A/U DS45104110(C)_01_0906



**Kioti Tractor/
Daedong Industrial Co., Ltd.**
1422-5, Seocho-Dong, Seocho-Ku, Seoul, Korea
tel 82-2-3470-7454-9 fax 82-2-3470-7485
web www.daedong.co.kr

Dealer Imprint Area

Part Number LIT-DS-ALL



Exceptional quality and features in the DS series tractors

Keeps you *ahead of the pack*



Tractor Model - DS4510



One Side Service

The smart one side service design, lets you service the fuel filter, fuel system, engine oil filter, fill the oil and even change the air filter from the right side of the tractor.

Easy Open Hood


Easily open the hood with the touch of just one knob.

Innovative Design

The slanted hood design on the DS series tractors ensures the best visibility in its class as well as creating an attractive, sleek profile.

High Flow Hydraulic Pump

With a high flow hydraulic pump, performing multiple functions with either the backhoe or loader is simple with power to spare.



Independent PTO

The electro-hydraulic PTO clutch allows you to turn the PTO ON and OFF with just a simple flip of a switch. A safety start switch prevents starting the tractor while the PTO is engaged.



Front Axle

A field proven front axle design ensures durability and strength for loader operations.

Lift Capacity

With a lift of 2,425 lbs., the DS series Cat. 1 three point hitch has power to spare when carrying large implements, such as brush cutters, mowers and blades.

Heavy Duty Transmission

The heavy duty design of the DS series transmission adds strength to the tractor chassis and provides excellent draw bar pull.

DS Series

The DS series tractors are ready for any job that demands a durable tractor. An efficient engine, powerful lift capacity, convenient shuttle transmission, and sleek design makes the DS series tractor a great value.

Foldable ROPS

A fold-down roll bar makes it quick and easy to move in low clearance areas.

Power Steering

Responsive, powerful and comfortable steering reduces operator fatigue. The power steering system is robustly designed for maneuvering in soft soil and for front loader operation.

