

HOLDER

NO COMPROMISES



HOLDER F 560

TECHNICAL DATA HOLDER F 560

Characteristics	Engine	Deutz four-stroke diesel
	Power output	45,9 kW (62 HP)
	Cylinders	4
	Cooling	Integrated oil-air cooling
	Air filter	Dry air filter with acoustic warning apparatus
	Tank capacity	51 l
	Drive	12/12 reverse gear unit
	Differential lock	Front and rear, simultaneously electronically switchable, easy to operate with the toggle switch, 100% effective for both axles
	Max. speed	35 km/h
	Power take-offs	load-dependent, independent engine power take-off, front/rear
	Brakes	hydraulically activated wet multi-plate brake/mechanical handbrake
	Steering	Full hydrostatic articulated-frame steering (load-sensing)
	Hydraulic system/pump	14 ccm/U or 37 l/min
	Hydraulic oil quantity	18 l
	Excavation power, front/rear	700/1.800 kg, KAT IN and KAT I
Weight ¹	Auxiliary control valves	Extensive expansion possibilities designed for the respective usage
	Activated carbon filter and air conditioning	optional
	Empty weight	1.869 - 2.075 kg
	Gross vehicle weight	2.800 kg
	Gross axle weight rating, front/rear	1.700 kg
	Coupling load	600 kg
	Wheel base	1.448 mm
	Total length with rear three-point hitch	3.309 mm
Dimensions	Total height with cabin ²	2.010 - 2.080 mm
	Total height with folding bracket ²	2.070 - 2.140 mm
	Track ²	701 - 1.144 mm
	Narrowest total exterior width ²	925 mm

¹ incl. driver with 75 kg, depending upon tyres and equipment ² depending upon tyres

A HOLDER IS ALWAYS ECONOMICAL

Those who can count can't get around a Holder: The Holder may cost more to purchase than other vehicles, but it is considerably more economical over the long term: The high quality ensures a long service life, and thereby reduced repair costs and less idle time. The resale value is also considerably higher than that for other vehicles. A Holder is an investment that pays.

STANDARD HOLDER ADVANTAGES



Versatility



Articulated-frame steering



Real four-wheel drive



Wheel load balance



Four wheels of equal size

THE MANOEUVRABLE HAULER

With its short front end, the deep-drawn bonnet and the especially narrow total width, the Holder F 560 is not only extremely manoeuvrable; it also offers the best overview for all work.

It can really show its superiority in the vineyard: With the continuous four-wheel drive, very high climbing performance is achieved. Due to the wheel load balance, the machine demonstrates the best stability, even on bluffs. The four equal sized wheels thereby ensure optimal soil conservation.

Optimal consultation, sales and service from your Holder partner:

Max Holder GmbH

Max-Holder-Straße 1
72555 Metzingen
Germany

Telephone: +49 7123 966-0
Fax: +49 7123 966-213

info@max-holder.com
www.max-holder.com